



PCN / EOL Notification

Product Change Notification Number: **CC070302A (Revised)**

Date: January 24, 2007

See Bold Blue Text Below And The Attachment A

Title: AT24C512 DIE SHRINK

Product Identification:

All Wafers, Packages and Voltages of the AT24C512, Industrial Temperature Grade (-40C to +85C). **See Attachment A**

Reason for Change:

☒ Design

☐ Manufacturing Location

☐ Processing

☐ Quality/Reliability

☐ Logistics

☐ Material

Change Description:

Atmel has performed a die size reduction of the AT24C512 in the Industrial Temperature (-40 to +85C). The new version device will be manufactured utilizing the .25u process versus the .35u process for the current AT24C512. A NEW part number will be created by adding "B" to the suffix of the part identifier for the shrink: AT24C512B.

Atmel has also optimized the clock frequency at lower Vcc, and the new AT24C512B will operate at 400kHz at 1.8V & 1MHz at 2.5V versus 100kHz at 1.8V & 400kHz at 2.5V for the current AT24C512 device. In addition, an extra device address pin (A2) has been added for expanded cascability.

The new packaged devices will be offered in 1.8 and 2.5 voltages: (1.8V to 3.6V) and (2.5V to 3.6V). The dBGA2, die, and wafer sales will only be offered in 1.8V.

To accommodate the growing movement to Lead-Free products, the new shrink will ONLY be available in Pb-Free (Green) / Halogen-Free packaging. The 8-SOIC, 8-TSSOP, and 8-ULTRA THIN SAP packages with NiPdAu lead finish will be designated by "H" in the catalogue part number. The 8-lead PDIP and dBGA2 with the Matte Tin lead finish will be designated by "U" in the catalogue part number.

New physical part marking scheme:

8-SOIC (1.8V)

TOP MARK

Seal Year

Y = SEAL YEAR

WW = SEAL WEEK

| Seal Week

6: 2006 0: 2010

02 = Week 2

| | |

7: 2007 1: 2011

04 = Week 4

| --- | --- | --- | --- | --- | --- | --- | --- |

8: 2008 2: 2012

:: : :::: :

A T M L H Y W W

9: 2009 3: 2013

:: : :::: ::

| --- | --- | --- | --- | --- | --- | --- | --- |

50 = Week 50

2 F B 1

52 = Week 52

| --- | --- | --- | --- | --- | --- | --- | --- |

* Lot Number

Lot Number to Use ALL Characters in Marking

| --- | --- | --- | --- | --- | --- | --- | --- |

BOTTOM MARK

|

Pin 1 Indicator (Dot)

No Bottom Mark

8-SOIC (2.5V)

TOP MARK

```

Seal Year
| Seal Week
| | |
|---|---|---|---|---|---|---|---|
A T M L H Y W W
|---|---|---|---|---|---|---|---|
2 F B 2
|---|---|---|---|---|---|---|---|
* Lot Number
|---|---|---|---|---|---|---|---|
|
Pin 1 Indicator (Dot)

```

Y = SEAL YEAR

```

6: 2006 0: 2010
7: 2007 1: 2011
8: 2008 2: 2012
9: 2009 3: 2013

```

WW = SEAL WEEK

```

02 = Week 2
04 = Week 4
:: : :::: :
:: : :::: ::
50 = Week 50
52 = Week 52

```

Lot Number to Use ALL Characters in Marking

BOTTOM MARK

No Bottom Mark

8-TSSOP (1.8V)

TOP MARK

Pin 1 Indicator (Dot)

```

|
|---|---|---|---|
* H Y W W
|---|---|---|---|
2 F B 1
|---|---|---|---|

```

Y = SEAL YEAR

```

6: 2006 0: 2010
7: 2007 1: 2011
8: 2008 2: 2012
9: 2009 3: 2013

```

WW = SEAL WEEK

```

02 = Week 2
04 = Week 4
:: : :::: :
:: : :::: ::
50 = Week 50
52 = Week 52

```

BOTTOM MARK

```

|---|---|---|---|---|---|
P H
|---|---|---|---|---|---|
A A A A A A A
|---|---|---|---|---|---|
<- Pin 1 Indicator

```

8-TSSOP (2.5V)

TOP MARK

Pin 1 Indicator (Dot)

```

|
|---|---|---|---|
* H Y W W
|---|---|---|---|
2 F B 2
|---|---|---|---|

```

Y = SEAL YEAR

```

6: 2006 0: 2010
7: 2007 1: 2011
8: 2008 2: 2012
9: 2009 3: 2013

```

WW = SEAL WEEK

```

02 = Week 2
04 = Week 4
:: : :::: :
:: : :::: ::
50 = Week 50
52 = Week 52

```

BOTTOM MARK

```

|---|---|---|---|---|---|
P H
|---|---|---|---|---|---|
A A A A A A A
|---|---|---|---|---|---|
<- Pin 1 Indicator

```

8-PDIP (1.8V)

TOP MARK

Seal Year							
Seal Week							
---	---	---	---	---	---	---	---
A	T	M	L	U	Y	W	W
---	---	---	---	---	---	---	---
2	F	B		1			
---	---	---	---	---	---	---	---
*	Lot Number						
---	---	---	---	---	---	---	---
Pin 1 Indicator (Dot)							

Y = SEAL YEAR WW = SEAL WEEK

6: 2006	0: 2010	02 = Week 2
7: 2007	1: 2011	04 = Week 4
8: 2008	2: 2012	:: : :::: :
9: 2009	3: 2013	:: : :::: ::
		50 = Week 50
		52 = Week 52

Lot Number to Use ALL Characters in Marking

BOTTOM MARK

No Bottom Mark

8-PDIP (2.5V)

TOP MARK

Seal Year							
Seal Week							
---	---	---	---	---	---	---	---
A	T	M	L	U	Y	W	W
---	---	---	---	---	---	---	---
2	F	B		2			
---	---	---	---	---	---	---	---
*	Lot Number						
---	---	---	---	---	---	---	---
Pin 1 Indicator (Dot)							

Y = SEAL YEAR WW = SEAL WEEK

6: 2006	0: 2010	02 = Week 2
7: 2007	1: 2011	04 = Week 4
8: 2008	2: 2012	:: : :::: :
9: 2009	3: 2013	:: : :::: ::
		50 = Week 50
		52 = Week 52

Lot Number to Use ALL Characters in Marking

BOTTOM MARK

No Bottom Mark

8-Ultra Thin SAP (1.8V)

TOP MARK

Seal Year							
Seal Week							
---	---	---	---	---	---	---	---
A	T	M	L	H	Y	W	W
---	---	---	---	---	---	---	---
2	F	B		1			
---	---	---	---	---	---	---	---
Lot Number							
---	---	---	---	---	---	---	---
*							
Pin 1 Indicator (Dot)							

Y = SEAL YEAR WW = SEAL WEEK

6: 2006	0: 2010	02 = Week 2
7: 2007	1: 2011	04 = Week 4
8: 2008	2: 2012	:: : :::: :
9: 2009	3: 2013	:: : :::: ::
		50 = Week 50
		52 = Week 52

dBGA2

TC = TRACE CODE (ATMEL LOT
NUMBERS TO CORRESPOND
WITH ATK TRACE CODE LOG BOOK)

There will be a NEW part number created by adding a “B” to the suffix of the catalogue part number: The AT24C512 will now be AT24C512**B**.

Qualification Data: ☒ available ☐ will be available ☐ not applicable

Samples: ☒ available ☐ will be available ☐ not applicable

The new devices are a form, fit and function equivalent of the current devices, which meet all databook specifications.

Proposed First Ship Date: April 24, 2007
Last Time Buy Date: July 24, 2007
Last Ship Date: January 24, 2008

All orders placed after the notification date are non-cancellable and non-returnable (NCNR).

Atmel Contact: pcnadm@atmel.com

Atmel will deem this change accepted unless specific conditions of acceptance are provided in writing within 30 days from the date of this notice. All correspondence must be sent to the Quality Contact e-mail address listed above.

Information provided herein is in connection with Atmel products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Atmel's Terms and Conditions of Sale for such products, Atmel assumes no liability whatsoever, and Atmel disclaims any express or implied warranty, including liability or warranties relating to fitness for a particular purpose, merchantability, or non-infringement of any patent, copyright or other intellectual property right. Atmel products are not intended for use in a product or system intended to support or sustain life which, if it fails, can be reasonably expected to result in significant personal injury. Atmel may make changes to specifications and product descriptions at any time, without notice.

Attachment A

Current Part Number	Replacement Part Number
AT24C512-10PU-1.8	AT24C512B-PU (Bulk Only)
AT24C512-10PU-2.7	AT24C512B-PU25 (Bulk Only)
AT24C512-10TU-1.8 BULK	AT24C512B-TH-B
AT24C512-10TU-1.8 SL383 (T&R)	AT24C512B-TH-T (5k per reel)
AT24C512-10TU-2.7 BULK	AT24C512B-TH25-B
AT24C512-10TU-2.7 SL383 (T&R)	AT24C512B-TH25-T (5k per reel)
AT24C512-W1.8-11	AT24C512B-W-11
AT24C512-W1.8-27	AT24C512B-W-11
AT24C512-W2.7-11	AT24C512B-W-11
AT24C512-W2.7-7	AT24C512B-W-11
AT24C512-WB1.8-11	AT24C512B-WU-11 (Green only)
AT24C512-WU1.8-11	AT24C512B-WU-11
AT24C512W-10SU-1.8 BULK	AT24C512BW-SH-B
AT24C512W-10SU-1.8 SL383 (T&R)	AT24C512BW-SH-T (2k per reel)
AT24C512W-10SU-2.7 BULK	AT24C512BW-SH25-B
AT24C512W-10SU-2.7 SL383 (T&R)	AT24C512BW-SH25-T (2k per reel)
AT24C512C1-10CU-1.8 SL383 (T&R)	AT24C512BY7-YH-T (5k per reel)
AT24C512C1-10CU-2.7 SL383 (T&R)	AT24C512BY7-YH25-T (5k per reel)
AT24C512N-10SU-1.8 BULK	AT24C512BN-SH-B
AT24C512N-10SU-1.8 SL383 (T&R)	AT24C512BN-SH-T (4k per reel)
AT24C512N-10SU-2.7 BULK	AT24C512BN-SH25-B
AT24C512N-10SU-2.7 SL383 (T&R)	AT24C512BN-SH25-T (4k per reel)
AT24C512U4-10UU-1.8 SL383 (T&R)	AT24C512BU2-UU-T (5k per reel)
AT24C512U4-10UU-2.7 SL383 (T&R)	AT24C512BU2-UU-T (5k per reel)